

STRUCTURAL FRAMING MEMBERS WITH INTEGRATED FLOW CHANNELS AND METHOD OF MAKING SAME

5

Background of the Invention

Technical Field

10

The invention relates generally to the field of composite structures, and more particularly to the framing members with integrated flow channels for use in certain manufacturing processes.

Description of the Related Art

15

20

A variety of manufacturing techniques are known for assembling composite structures. For example, the spray lay-up method has been used for many years with good success. In spray lay-up systems, chopped fiber together with a catalyzed resin is sprayed directly into an open mold. Structural reinforcing members such as stringers can be positioned in the mold prior to the application of the chopped fiber and resin for improving the overall strength and rigidity of the structure. For example, U.S. Patent Nos. 5,429,066, 5,800,749 and 5,664,518 to Lewit et al. describe various types of reinforcing members that can be used for this purpose. The fiber, resin and stringers applied in this way are then left to cure.

25

Recently, environmental concerns have encouraged the development of new closed mold manufacturing processes intended to limit the release of potentially harmful chemicals. These include resin transfer molding (RTM), vacuum assisted resin transfer molding (VARTM), and other similar processes in which fabrics are laid up in a mold as a dry stack of materials and then sealed in a mold or vacuum bagged. Resin is then allowed to flow into the dry stack of materials forming a laminate. Disposable tubing can be used exterior to the mold or vacuum bag for facilitating the injection of resin at desired locations.

One issue with closed mold manufacturing techniques involves the problem of ensuring adequate resin distribution over the whole laminate sufficiently quickly before the resin has cured substantially. In some closed mold systems, resin flow is aided by the use of a knitted type of non-structural fabric which is included in laminate specifically for this purpose. However, the additional labor and cost of materials with these approaches are such that the simple addition of non-structural fabric to the laminate has not entirely solved the problem of ensuring fast and complete distribution of resin. Accordingly, it would be desirable to provide a method and system for integrating a resin flow mechanism in composite structure manufacturing processes that minimizes the need for non-reusable external processing components (such as disposable tubing), and provides consistent results with only a minimal amount of additional time, labor and cost.

Summary of the Invention

The invention concerns a composite part, comprising an elongated foam core and a flow channel media attached to a first elongated side thereof. The flow channel media forms interstices for the passage of resin. At least one fabric layer is secured to the elongated foam core, and encloses a first elongated side of the foam core, including the flow channel media. In this way, a resin flow path is defined along the first elongated side. The fabric layer can further enclose at least a second and third elongated side of the foam core where, where each of the second and third elongated sides adjoin the first elongated side. Fabric tab portions can be provided extending from the second and third elongated sides for aiding in the installation of the composite part in a larger composite structure.

One more secondary flow channel can also be integrated into the composite part. In this regard, a flow channel media can also be attached to the elongated foam core and extend along a second elongated side thereof. As with the first flow channel media, the second flow channel media has interstices for the passage of resin therethrough. A fabric layer can enclose the second elongated side of the foam core, including the second flow channel media, to define a second resin flow path along the second elongated side. According to one aspect of the invention, the second elongated side can be opposed from the first elongated side.

The flow channel media as described herein can be bounded by another fabric layer interposed between the foam core and the flow channel media. That fabric layer can be a substantially closed fabric i.e., with low porosity for preventing a passage through the second fabric of foam into the flow channel media. The flow channel medium can be a plastic mesh with a large volume of open spaces between the fibers defining the mesh.

The invention also concerns a method of making a composite part with an

integrated flow channel. The method or process involves 1) arranging a fabric layer in a configuration constrained against outward movement and defining a cavity between opposing surfaces thereof, 2) arranging a flow channel media adjacent at least one of the opposing surfaces, 3) dispensing a predetermined amount of a self-expanding, self-curable, uncured structural foam into the cavity, and finally freeing the cured composite structure from the constraint of the arranging step. The fabric layer can be selected from the group consisting of glass fiber, carbon fiber, aramid fiber, linear polyethylene or polypropylene fiber, and polyethylene fiber.

Alternatively, the fabric may be polyester staple mat, glass fiber mat, organic fiber mat or inorganic fiber mat. The structural foam used herein for the foam core can be a two-part, self-expanding, self-curing polyurethane foam. The molding pressure of the foam can be controlled so that the foam penetrates at least partially into interstices of the fabric layers as it expands and cures.

Brief Description of the Drawings

Fig. 1 is a drawing useful for illustrating the structure of a composite part as described and claimed herein.

5 Fig. 2 is a drawing useful for illustrating the structure of a flow channel media and fabric covering.

Fig. 3 is a drawing useful for illustrating how the composite parts as described herein can be used in a closed molding process.

10 Fig. 4 is a flow chart useful for illustrating a process for manufacturing the composite part of Fig. 1.

Fig. 5 is a drawing useful for illustrating the process of Fig. 4.

Fig. 6 is a cross-sectional view along lines 6-6 in Fig. 5.

Detailed Description

Fig. 1 is a drawing useful for explaining the composite part according to a preferred embodiment of the invention. Composite part 100 comprises an elongated foam core 102 and a flow channel 316 formed by flow channel media 116 attached thereto along a first elongated side 106. A fabric layer 103 is secured to the elongated foam core 102 and encloses at least the elongated side 106 of the foam core 102. In this way, the fabric layer 103 and the flow channel media 116 define a resin flow path along the elongated side 106 of the composite part 100.

One or more additional flow channels can be provided on other elongated sides 104, 108, 110 of the composite part 100. According to a preferred at least a second flow channel can be provided along a side 110 of the composite part 100 forming a base thereof and opposed from the flow channel media 116. The second flow channel is comprised of a flow channel media 118 and can be enclosed by fabric layer 103 or a separate fabric layer 112. Further, it will be appreciated that the flow channel media does not necessarily need to be positioned adjacent a top or bottom side of the part 100. Instead, the flow channel media can be placed as dictated by a particular resin flow requirement. For example, the flow channel media can be placed spaced apart from opposing sides 106, 110 of the part 100 with structural foam 102 above and below the flow channel media.

The composite part 100 can further comprise fabric tab portions 114 extending from elongated sides 104, 108 along a portion thereof adjacent to the bottom or base side 110. The tab portions are useful for securing the composite part in a larger structure as shall hereinafter be described.

According to one embodiment, the foam core can be a structural foam. For example, a a two-part, self-expanding, self-curing urethane foam has been found to work well for this purpose. The fabric layers 103, 112 can be comprised of organic

or inorganic fibers. For example the fabric layers 103, 112 can be woven glass fiber, carbon fiber, aramid fiber, linear polyethylene or polypropylene fiber, or polyethylene fiber. Alternatively, the fabric layer can be a non-woven fabric such as polyester staple mat, glass fiber mat, organic fiber mat or inorganic fiber mat. Of course, those skilled in the art will appreciate that the fabric layers 103, 112 can each be formed of multiple layers of fabric, such as a combination of woven and non-woven fabric layers. These fabric layers can be attached to one another by any suitable means.

The flow channel media 116, 118 can be formed of any material not susceptible to chemical attack by liquid molding resin or urethane foam. For example, the flow channel media can preferably be a mesh material formed of polyester, nylon or high density polyethylene. However, those skilled in the art will recognize that any other suitable material, such as a wide variety of plastics, can be used for this purpose provided that they are not susceptible to chemical attack by either resin or foam as used in the fabrication of the composite structures as described herein. In any case, the flow channel media material preferably defines a substantial number of interstices or openings therein facilitating the passage and channeling of resin through the flow channel media with less resistance as compared to the fabrics layers 120, 103 and 112. The mesh material forming the flow channel media can be a three-dimensional matrix of fibers joined at the intersections thereof. According to a preferred embodiment about 50 to 95% of the matrix is open space. In this way, resin introduced under pressure will tend to flow through the flow channel 116, 118 substantially along the elongated sides of the composite part 100.

The flow channel media is preferably bounded by a fabric layer 120 interposed between the foam core 102 and the flow channel media 116, 118. For

example, the flow channel media 116, 118 can be arranged as shown in Fig. 2, encased within the fabric layer 120. The fabric layer can be comprised of a non-woven filter fabric made of materials such as polyester staple mat, glass fiber mat, organic fiber mat or inorganic fiber mat. The fabric layer 120 is useful in this arrangement for preventing the foam core from substantially penetrating into the interstices defined by the flow channel media 116, 118. However, the fabric layer 120 is not required and the invention can be used with only the flow channel media 116, 118 and the fabric layers 103, 110 defining the flow channels 316.

According to one embodiment, the flow channel media can be a three-dimensional core of extruded high-density nylon or polyester with a nonwoven filter fabric bonded to one or both sides. A product useful as flow channel media and including an outer fabric layer 120 is known as EnkaFusion™ that is commercially available from Colbond of Sand Hill Road, Enka, NC 28728.

According to a preferred embodiment, the fabrics 103, 120, 112 and flow channel media are preferably selected to achieve a controlled volume of channel flow and release of resin from the flow channel media 116, 118. More particularly, although it is desired for resin to pass through the flow channels 316, a certain amount of resin can be advantageously released from the flow channels 316 so as to wet-out the fabric forming fabric layers 103, 112 and tabs 114. In this way, resin can be quickly and efficiently be introduced along the length of the part 100 in a closed mold system.

The fabric layer 120 is also preferably selected with a porosity sufficient to prevent a passage of foam from the foam core 102 through the fabric 120 and into the flow channel media 116, 118. An introduction of excess foam into the flow channel media during the manufacturing process can restrict or prevent the flow of resin through the flow channel 316.

Fig. 3 shows a set of composite parts 100 arranged as stringers to form a structural reinforcement for a larger composite article, in this case a boat. The composite parts 100 can be arranged as shown in interlocking fashion. In Fig. 3, tabs 114 are omitted, but the invention is not limited in this regard. As shown in
5 Fig. 3, flow channels 316 are provided as previously described in relation to Figs. 1 and 2. By way of example, arrows 302 illustrate the direction of resin flow through each of the flow channels. Arrows 304 illustrate how a selectively controlled portion of the resin can be caused to flow down the sides of composite parts 100 to wet out the fabric layers. The amount of resin that flows out of the flow
10 channel in this way can be controlled by selection of the fabric layers enclosing the resin flow channel and the selection of flow channel media. For example, in the composite part in Figs. 1 and 2, the resin flow out of the flow channel would be determined by fabric layers 103, 120 and flow channel media 116, 118. Flow channel media 116, 118 with greater porosity and a more open mesh structure will
15 create less resistance to resin flow and therefore less tendency for resin to exit the flow channel. Conversely, fabric layers 103, 120 with less porosity will tend to increase the amount of resin exiting the flow channel 316. Resin flow can be advantageously further controlled by selectively injecting resin at any point along a flow channel. For example, the vacuum bag or mold can be penetrated at one or
20 more selected locations deemed advantageous for improved resin flow, and resin can be injected at that point.

Referring now to Fig. 4 - 6, the invention also concerns a method of making a composite part with an integrated flow channel. As illustrated by the flow chart in Fig. 4, the method can begin in step 400 by selecting flow channel media 116,
25 118 and fabrics 103, 112, 120 for desired volume of resin flow through flow channel 316 and for desired volume of resin dispensing along length of part 100.

In step 402, the process continues with the step of arranging a fabric layer 103, 112, 120 in a configuration constrained against outward movement and defining a cavity between opposing surfaces thereof. This arrangement can be achieved in either a simple molding process such as described in U.S. Patent No. 5,429,066 to
5 or using a continuous manufacturing process where foam, fabric and flow channel media are continuously fed into a die in an arrangement similar to that disclosed in U.S. Patent No. 5,897,818 to Lewit et al. Each of these issued patents are hereby incorporated herein by reference. However, those skilled in the art will appreciate that the invention is not limited in this regard.

10 The process continues in step 404 by arranging the flow channel media adjacent at least one of the opposing surfaces of the die or mold. According to a preferred embodiment, a flow channel media 116, 118 can be arranged on opposed surfaces 106 and 112. This can be achieved by simply placing the flow channel media within a mold or feeding a continuous layer of flow channel media 106 to a
15 location along an upper and lower opposed sides of the die. Referring to Figs. 5 and 6, flow channel media 116, 118 and associated fabrics 103, 112, and 120 can be fed into a die 506 using a conveyor 502 moving in a direction 508. For greater clarity, fabrics 112 and 120 are not shown in Fig. 5.

In step 406, a predetermined amount of a self-expanding, self-curable,
20 uncured structural foam is introduced into the cavity formed by a mold or die. In Fig. 5, the foam is injected into the cavity using a foam spray nozzle 504.

According to a preferred embodiment, in step 408 the foam is allowed to expand and cure in the cavity at a molding pressure. The molding pressure will be determined by the predetermined amount of foam introduced into the cavity.

25 Although not essential to the invention, the foam can be allowed to attach itself to the fabric layer and the flow channel media to form the composite structure.

According to a preferred embodiment, the foam attaches to the fabric layer 120 rather than directly to the flow channel media 116, 118.

Finally, in step 108 the composite part is removed from the mold or is allowed to pass out of the die as shown on the right side of Fig. 5. According to one embodiment, a molding pressure of the foam is controlled so that it penetrates at least partially into interstices of the fabrics 103, 112, 120 as it expands and cures. However, the invention is not limited in this regard and other molding pressures can also be used.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000